

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® RAPID RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy constituents

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40
E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Berlin: 0049 30 19 24 0 & 0049 30 30 68 6 7 11
Bonn: 0049 228 19 27 0 & 0049 228 28 7 3 32 11
Erfurt: 0049 361 73 07 30
Freiburg: 0049 761 16 24 0
Göttingen: 0049 51 19 24 0 & 0049 551 38 31 80
Homburg: 0049 6841 19 24 0
Mainz: 0049 6131 19 24 0 & 0049 6131 23 24 66
München: 0049 89 19 24 0
Nürnberg: 0049 911 39 8 2 45 1
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	26.10.2020	400001021215	02.08.2018
			Date of first issue: 06.12.2017

Print Date 30.08.2021

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,
Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

:



Signal word

: Warning

Hazard statements

:	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

:	Prevention:	
	P261	Avoid breathing mist or vapours.
	P264	Wash skin thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ eye protection/ face protection.
	Response:	
	P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
	P391	Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

1,4-Bis(2,3-epoxypropoxy)butane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 70 - < 90

ARALDITE® RAPID RESIN

Version 1.2 Revision Date: 26.10.2020 SDS Number: 400001021215 Date of last issue: 02.08.2018
Date of first issue: 06.12.2017

Print Date 30.08.2021

	01-2119456619-26	Aquatic Chronic 2; H411	
1,4-Bis(2,3-epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	$\geq 3 - < 10$

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Halogenated compounds

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	26.10.2020	400001021215	02.08.2018
			Date of first issue: 06.12.2017

Print Date 30.08.2021

Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Storage class (TRGS 510) : 10, Combustible liquids

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m3
	Workers	Dermal	Long-term systemic effects	0,75 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESINVersion
1.2Revision Date:
26.10.2020SDS Number:
400001021215Date of last issue: 02.08.2018
Date of first issue: 06.12.2017

Print Date 30.08.2021

				bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
1,4-Bis(2,3-epoxypropoxy)butane	Workers	Inhalation	Long-term systemic effects	4,7 mg/m3
	Workers	Dermal	Long-term systemic effects	6,66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,16 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,33 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
Remarks:	Assessment Factors	
	Marine water	0,001 mg/l
	Assessment Factors	
	Fresh water sediment	0,341 mg/kg dry weight (d.w.)
	Equilibrium method	
	Marine sediment	0,034 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	0,065 mg/kg dry weight (d.w.)
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg
1,4-Bis(2,3-epoxypropoxy)butane	Fresh water	0,024 mg/l
	Assessment Factors	
	Marine water	0,002 mg/l
	Assessment Factors	

ARALDITE® RAPID RESIN

Version 1.2 Revision Date: 26.10.2020 SDS Number: 400001021215 Date of last issue: 02.08.2018
Date of first issue: 06.12.2017

Print Date 30.08.2021

	Sewage treatment plant	100 mg/l
	Assessment Factors	
	Fresh water sediment	0,084 mg/kg dry weight (d.w.)
	Equilibrium method	
	Marine sediment	0,008 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	0,003 mg/kg dry weight (d.w.)
	Equilibrium method	
	Oral	0,028 mg/kg

8.2 Exposure controls

Personal protective equipment

- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines
- Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : No data is available on the product itself.
- Odour : No data is available on the product itself.
- Odour Threshold : No data is available on the product itself.
- pH : No data is available on the product itself.
- Melting point/freezing point : No data is available on the product itself.

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Boiling point	: No data is available on the product itself.
Flash point	: No data is available on the product itself.
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: No data is available on the product itself.
Relative vapour density	: No data is available on the product itself.
Relative density	: No data is available on the product itself.
Density	: No data is available on the product itself.
Solubility(ies)	
Water solubility	: No data is available on the product itself.
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Decomposition temperature	: No data is available on the product itself.
Viscosity	: No data is available on the product itself.
Explosive properties	: No data is available on the product itself.
Oxidizing properties	: No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 2 000 mg/kg
Method: Calculation method

Acute inhalation toxicity - Product : Acute toxicity estimate : > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity - Product : Acute toxicity estimate : > 2 000 mg/kg
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Exposure time: 4 h

Assessment: Irritating to skin.

Method: OECD Test Guideline 404

Result: Irritating to skin.

1,4-Bis(2,3-epoxypropoxy)butane:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Serious eye damage/eye irritation

Product:

Species: Not Assigned

Method: OECD Test Guideline 437

Result: Eye irritation

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: The product is a skin sensitiser, sub-category 1B.

1,4-Bis(2,3-epoxypropoxy)butane:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

GLP: yes

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

: Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)

Result: negative

1,4-Bis(2,3-epoxypropoxy)butane:

Genotoxicity in vitro : Test Type: reverse mutation assay

Concentration: 10 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

GLP: yes

Remarks: Not classified due to data which are conclusive although insufficient for classification.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	26.10.2020	400001021215	02.08.2018
			Date of first issue: 06.12.2017

Print Date 30.08.2021

: Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster lung cells
Concentration: 1 - 100 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive
GLP: yes
Remarks: Not classified due to data which are conclusive although insufficient for classification.

: Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster lung cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive
GLP: no
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo

: Test Type: in vivo assay
Test species: Mouse (male)
Cell type: Germ
Application Route: Oral
Dose: 3333, 10000 mg/kg
Result: negative

Test Type: gene mutation test
Test species: Rat (male)
Cell type: Somatic
Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

1,4-Bis(2,3-epoxypropoxy)butane:

Genotoxicity in vivo

: Test Type: In vivo micronucleus test
Test species: Mouse (male)
Cell type: Somatic
Application Route: Oral
Exposure time: 4 d
Dose: 187.5 - 750 mg/kg
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Test Type: unscheduled DNA synthesis assay

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Test species: Rat
Cell type: Liver cells
Application Route: Oral
Method: OECD Test Guideline 486
Result: negative

Components:

1,4-Bis(2,3-epoxypropoxy)butane:

Germ cell mutagenicity- : Weight of evidence does not support classification as a germ
Assessment cell mutagen., Animal testing did not show any mutagenic
effects.

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male
Application Route: Oral
Exposure time: 24 month(s)
Dose: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment: 7 days/week
No observed adverse effect level: 15 mg/kg bw/day
Method: OECD Test Guideline 453
Result: negative
Target Organs: Digestive organs

Species: Mouse, male
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0, 0.1, 10, 100 mg/kg bw/day
Frequency of Treatment: 3 days/week
No-observed-effect level: 0,1 mg/kg body weight
Method: OECD Test Guideline 453
Result: negative
Target Organs: Digestive organs

Species: Rat, female
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0.1, 100, 1000 mg/kg bw/day
Frequency of Treatment: 5 days/week
No-observed-effect level: 100 mg/kg body weight
Method: OECD Test Guideline 453
Result: negative

Species: Rat, female
Application Route: Oral
Exposure time: 24 month(s)
Dose: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment: 7 days/week
No observed adverse effect level: 100 mg/kg bw/day
Method: OECD Test Guideline 453

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Result: negative
Target Organs: Digestive organs

Species: Rat, females
Application Route: Oral
Exposure time: 24 month(s)
Dose: 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment: 7 days/week
No-observed-effect level: 2 mg/kg bw/day
Method: OECD Test Guideline 453
Result: negative
Target Organs: Digestive organs

Carcinogenicity - : No data available
Assessment

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 milligram per kilogram
Duration of Single Treatment: 238 d
Frequency of Treatment: 1 daily
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
General Toxicity F1: No-observed-effect level: 750 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
Dose: 0, 30, 100 or 300 milligram per kilogram
Duration of Single Treatment: 28 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: 300 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
60 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: >
540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

1,4-Bis(2,3-epoxypropoxy)butane:

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0/30/100/300 mg/kg bw/day
Duration of Single Treatment: 17 d
General Toxicity Maternal: No observed adverse effect level:
300 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
300 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes
Remarks: Information given is based on data obtained from
similar substances.

Reproductive toxicity - : No data available
Assessment

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Species: Rat, male and female
NOAEL: 50 mg/kg
Application Route: oral (gavage)
Exposure time: 14 Weeks Number of exposures: 7 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Dose: 0, 50, 250, 1000 mg/kg/day
Method: OECD Test Guideline 408

Species: Rat, male and female
NOAEL: ≥ 10 mg/kg
Application Route: Skin contact
Exposure time: 13 WeeksNumber of exposures: 5 d
Dose: 0, 10, 100, 1000 mg/kg/day
Method: OECD Test Guideline 411

Species: Mouse, male
NOAEL: 100 mg/kg
Application Route: Skin contact
Exposure time: 13 WeeksNumber of exposures: 3 d
Dose: 0, 1, 10, 100 mg/kg/day
Method: OECD Test Guideline 411

1,4-Bis(2,3-epoxypropoxy)butane:
Species: Rat, male and female
NOAEL: 200 mg/kg
Application Route: Oral
Exposure time: 28 dNumber of exposures: daily
Dose: 25, 100, 200, 400 mg/kg
Method: Subacute toxicity

Species: Rat, male and female
NOAEL: 263 mg/kg
Application Route: Oral
Exposure time: 90 hNumber of exposures: daily
Dose: 0,30,100,300 mg/kg bw/day
Method: OECD Test Guideline 408
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Repeated dose toxicity - : No data available
Assessment

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	26.10.2020	400001021215	02.08.2018
			Date of first issue: 06.12.2017

Print Date 30.08.2021

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
aquatic invertebrates : Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 : 11 mg/l
plants : Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

NOEC : 4,2 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other : NOEC: 0,3 mg/l
aquatic invertebrates : Exposure time: 21 d
(Chronic toxicity) : Species: Daphnia magna (Water flea)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1,4-Bis(2,3-epoxypropoxy)butane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l
End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 203
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 75 mg/l
End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 202
GLP: no

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 160 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes

NOELR (Pseudokirchneriella subcapitata (green algae)): 40 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 209
GLP: no

12.2 Persistence and degradability

Components:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	26.10.2020	400001021215	02.08.2018
			Date of first issue: 06.12.2017

Print Date 30.08.2021

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

1,4-Bis(2,3-epoxypropoxy)butane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 43 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

Test Type: aerobic
Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 38 %
Related to: Dissolved organic carbon (DOC)
Exposure time: 28 d
Method: OECD Test Guideline 301E
GLP: no

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	26.10.2020	400001021215	02.08.2018
			Date of first issue: 06.12.2017

Print Date 30.08.2021

1,4-Bis(2,3-epoxypropoxy)butane:

Partition coefficient: n-octanol/water : log Pow: -0,269 (25 °C)
pH: 6,7
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

1,4-Bis(2,3-epoxypropoxy)butane:

Distribution among environmental compartments : Koc: 12,59
Method: OECD Test Guideline 121

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

IATA

14.1 UN number : UN 3082
14.2 UN proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo aircraft) : 964

Packing instruction (passenger aircraft) : 964

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

IMDG

14.1 UN number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

EmS Code : F-A, S-F

14.5 Environmental hazards

Marine pollutant : yes

ADR

14.1 UN number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

14.5 Environmental hazards

Environmentally hazardous : yes

RID

14.1 UN number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL
HAZARDS

Water contaminating class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:
Not applicable
: Inorganic substances in powdered form:
Not applicable
: Inorganic substances in vapour or gaseous form:
Not applicable
: Organic Substances:
Not applicable
: Carcinogenic substances:
Not applicable
: Mutagenic:
Not applicable
: Toxic to reproduction:
Not applicable

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	26.10.2020	400001021215	02.08.2018
			Date of first issue: 06.12.2017

Print Date 30.08.2021

NZIoC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

Further information

Classification of the mixture:

Classification procedure:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® RAPID RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 02.08.2018
1.2	26.10.2020	400001021215	Date of first issue: 06.12.2017

Print Date 30.08.2021

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Based on product data or assessment
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.